

Wöhler DP 600 dichtheidsmeter

TECHNISCHE GEGEVENS

Druk

Meetbereik.....	± 7.000 Pa
Resolutie.....	0,1 Pa (< ± 900 Pa), anders 1 Pa
Nauwkeurigheid.....	± 0,5 Pa, anders ± 2,5 %Rdg

Volumestroom zonder adapter

Meetbereik.....	0,0 tot 200,0 Nm ³ /h
Resolutie.....	0,1 Nm ³ /h
Nauwkeurigheid.....	± 2,5 Nm ³ /h, anders ± 5 %Rdg

Volumestroom Adapter 3,0

Meetbereik.....	0,00 tot 10,00 Nm ³ /h
Resolutie.....	0,01 Nm ³ /h
Nauwkeurigheid.....	± 0,05 Nm ³ /h, anders ± 5 %Rdg

Volumestroom met adapter 0,3

Meetbereik.....	0,10 tot 18,00 NI/min
Resolutie.....	0,01 NI/min
Nauwkeurigheid.....	± 0,05 NI/min, anders ± 5 %Rdg

Overige specificaties

Gewicht	9,2 kg
Afmetingen	33 x 36 x 15 cm
Voeding	110 tot 230 V, 50 tot 60 Hz